















Données Techniques - Specifications


	 cond	 comp. W	 ABS. W	 Fuse	 Kwh/100Kg	 l / h	 kg	 Lbs	 kg	 Lbs	 Ton CO2 equiv.
CS20 A		559	440	10	51.1	2,46	28	62	33	73	0,286
CS20 W		559	360	10	38.0	28,1	28	62	33	73	0,260

24h Production Glace - Ice Production

Refroidissement à air - Air Cooled Unit

Temp. Air Air Temp.		Temp. Eau / Water Temp.			
°C	32°	21°	15°	10°	
°F	90°	70°	60°	50°	
10°	18	19	20	21	
50°	40	42	44	46	
21°	16.5	17.5	18.5	19.5	
70°	36	39	41	43	
32°	14	15	16	17	
90°	31	33	35	37	
38°	11	12	13	14	
100°	24	26	29	31	

Refroidissement à eau - Water Cooled Unit

Temp. Air Air Temp.		Temp. Eau / Water Temp.			
°C	32°	21°	15°	10°	
°F	90°	70°	60°	50°	
10°	18	19	20	21	
50°	40	42	44	46	
21°	16	17	18	19	
70°	35	37	40	42	
32°	15.5	16.5	17.5	18.5	
90°	34	36	39	41	
38°	13	14	15	16	
100°	29	31	33	35	



PANNEAU DE CONTRÔLE - CONTROL PANEL



Interrupteur On/Off
Switch On/Off


Size ice regulation screw
Vis de réglage
dimension des glaçons


CAPACITE DE STOCKAGE - BIN CAPACITY

6,5 Kg - 14,3 lbs | 325 pcs


DIMENSIONS - DIMENSIONS

LxPxH (mm / inch)

 340 x 480 x 600
13" 6/16x 19" 14/16 x 24" 10/16

 400 x 530 x 760
16" 12/16 x 21" 14/16 x 30" 15/16

TYPE DE GLAÇONS - ICE TYPE



20g
WEIGHT ICE
POIDS GLACE



18
PCS / CYCLE
PZ/CICLO

COND. UTILISATIONS - OPERATING REQUIREMENTS





Chaleur rejetée / Rejected Heat 977 W

Volume Air / Air Volume 185 m³/h



220-240/50/1

R134a GWP = 1430

MIN		MAX
10°C (50°F)		40°C (104°F)
5°C (41°F)		35°C (95°F)
- 10 %		+ 10 %
1 Bar (14 psi)		5 Bar (70 psi)

